


This document contains proprietary information and such information may not be disclosed to others for any purposes,
not used for sales/marketing/procurement purposes without written permission



1 Electrical

1.1 Impedence	50 Ω
1.2 Frequency	DC~18GHz
1.3 VSWR	1.30:1

2 Environmental&Mechanical

2.1 Temperature range	-40℃~+125℃
2.2 RoHs Compliant	
2.3 Durability	>500 cycles

3 Materials&plating

3.1 Body:	Brass; gold plated
3.2 Insulator:	Teflon
3.3 Contact Pin:	Bronze, gold plated
3.4 Nut:	Brass; gold plated

Tel:Lee13890694956

Web:www.hltchips.com

Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: H.wei 19/03/17
ENGINEER: L.yu 19/03/17
APPROVED: W.yi 19/03/17
TOLERANCES UNLESS OTHERWISE SPECIFIED
X ±0.50
.X ±0.20
.XX ±0.10
ANGLES ±1°

TITLE:
RF Termination
RP SMA Female Conn.
Termination 1 Watts

PART NO: HL-RPSMA-50KR



DIMENSION IN MILLIMETERS (mm)

SIZE: A4	SCALE: N/A	SHEET: 1/1	REV: A
----------	------------	------------	--------